

P/N NAS1081-3A12

Military-Fasteners.com

### Description

Fastener Length: 3/4", Thread: 10-32, Head Width: 3/32", Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS10813A12
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-655-9827
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1081-3A12 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Headless (setscrew)
Locking Feature:	Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

## How to Order

Order this setscrew from our inventory online by visiting <u>https://military-fasteners.com/collars/pin\_rivet+collars/NAS1081-3A12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.