



Military-Fasteners.com

P/N NAS1081-3A4L

Description


Fastener Length: 1/4", Thread: 10-32, Head Width: 3/32", Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS10813A4L |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-339-8591 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1081-3A4L Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.0937 Inches Minimum And 0.0947 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4047h Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1081 Professional/industrial Association Standard |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/NAS1081-3A4L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.