

## P/N NAS1081-4A14

### **Description**

Fastener Length: 7/8", Thread: 1/4-28, Head Width: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS10814A14

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-162-8516

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1081-4A14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.862 Inches Minimum And 0.888 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1081 Professional/industrial Association Standard

## **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/NAS1081-4A14">https://military-fasteners.com/collars/pin\_rivet+collars/NAS1081-4A14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.