

Description

Fastener Length: 1/8", Thread: 2-56, Head Width: 1/32", Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1081C02A2L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-119-6425
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1081C02A2L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Fastener Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.035 Inches Nominal
Thread Quantity Per Inch:	56
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Astma582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1081 Professional/Industrial Association Standard

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C02A2L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.