

Description

Fastener Length: 1/8", Thread: 6-32, Head Width: 1/32", Thread Length: 1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1081C06D2
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-501-2342
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1081C06D2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.047 Inches Minimum And 0.067 Inches Maximum
Fastener Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.0350 Inches Minimum And 0.0355 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1081 Professional/industrial Association Standard

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C06D2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.