

Description

Fastener Length: 3/16", Thread: 8-32, Head Width: 5/64", Thread Length: 7/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1081C08A3
Minimum Qty (MOQ):	10
NSN:	5305-01-024-2443
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1081C08A3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.103 Inches Minimum And 0.123 Inches Maximum
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1081 Professional/industrial Association Standard

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/NAS1081C08A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.