

**Description**

Fastener Length: 5/16", Thread: 10-32, Head Width: 15/16", Thread Length: 15/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1081C3D5L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-030-4007
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1081C3D5L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.220 Inches Minimum And 0.240 Inches Maximum
<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Cup
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.0937 Inches Minimum And 0.947 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Material Document And Classification:</b>	Mil-s-7720 Comp 303s Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1081 Professional/industrial Association Standard

## How to Order

Order this setscrew from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/NAS1081C3D5L](https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C3D5L) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.