

Description

Fastener Length: 5/16", Thread: 10-32, Head Width: 15/16", Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1081C3D5L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-030-4007
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1081C3D5L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.240 Inches Maximum
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.947 Inches Maximum
Thread Quantity Per Inch:	32
Material Document And Classification:	Mil-s-7720 Comp 303s Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1081 Professional/industrial Association Standard

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C3D5L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.