

Description

Fastener Length: 5/8", Thread: 1/4-28, Head Width: 1/8", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1081C4A10 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-044-0736 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1081C4A10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.614 Inches Minimum And 0.636 Inches Maximum |
| Fastener Length: | 0.614 Inches Minimum And 0.636 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.125 Inches Minimum And 0.127 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Material: | Steel Comp 303 Overall Or Steel Comp 303se Overall |
| Material Document And Classification: | Astm A582 Assn Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1081 Professional/Industrial Association Standard |

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C4A10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.