# P/N NAS1081C4A5

## Description

Fastener Length: 5/16", Thread: 1/4-28, Head Width: 1/8", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

| | |
|---|---|
| SKU / Model: | NAS1081C4A5 |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5305-01-045-0084 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

# P/N NAS1081C4A5 Specifications

| | |
|---|---|
| **Thread Class:** | 3a |
| **Thread Direction:** | Right-hand |
| **Thread Length:** | 0.302 Inches Minimum And 0.322 Inches Maximum |
| **Fastener Length:** | 0.302 Inches Minimum And 0.322 Inches Maximum |
| **Head Style:** | Headless (setscrew) |
| **Locking Feature:** | Patch Threads Or Pellet Threads Or Strip Threads |
| **Point Style:** | Flat |
| **Internal Drive Style:** | Hexagon |
| **Nominal Thread Diameter:** | 0.250 Inches |
| **Width Across Flats:** | 0.125 Inches Minimum And 0.127 Inches Maximum |
| **Thread Quantity Per Inch:** | 28 |
| **Material:** | Steel Comp 303 Overall Or Steel Comp 303se Overall |
| **Material Document And Classification:** | Astm A582 Assn Std All Material Responses Overall |
| **Surface Treatment:** | Passivate Overall |
| **Surface Treatment Document And Classification:** | Qq-p-35 Fed Spec Single Treatment Response Overall |
| **Thread Series Designator:** | Unjf |
| **Specification/standard Data:** | 80205-nas1081 Professional/industrial Association Standard |

## How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081C4A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.