

**Description**

Fastener Length: 53/64", Thread: 8-32, Thread Length: 51/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1096213                                |
| Minimum Qty (MOQ):      | 100 EA                                    |
| NSN:                    | 5305-00-490-0385                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1096-2-13 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.670 Inches Minimum And 0.811 Inches Maximum         |
| <b>Fastener Length:</b>                                     | 0.796 Inches Minimum And 0.843 Inches Maximum         |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.096 Inches Minimum And 0.110 Inches Maximum         |
| <b>Width Between Flats:</b>                                 | 0.241 Inches Minimum And 0.250 Inches Maximum         |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                   |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch                         |
| <b>Hardness Rating:</b>                                     | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum   |
| <b>Screw Material:</b>                                      | Steel Comp 4037                                       |
| <b>Screw Material Document And Classification:</b>          | Ams 6300 Assn Std Single Material Response            |
| <b>Screw Surface Treatment:</b>                             | Cadmium   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| <b>Thread Series Designator:</b>                            | Unc   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1096-2-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.