

**Description**

Fastener Length: 1-7/32", Thread: 8-32, Thread Length: 1-3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1096219
Minimum Qty (MOQ):	100 EA
NSN:	5305-00-943-2618
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1096-2-19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.046 Inches Minimum And 1.187 Inches Maximum
<b>Fastener Length:</b>	1.172 Inches Minimum And 1.219 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.096 Inches Minimum And 0.110 Inches Maximum
<b>Width Between Flats:</b>	0.241 Inches Minimum And 0.250 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1096-2-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.