

Description

length: 3/8", thread: 8-32, hex head, recessed, full thread, cadmium plated alloy steel, NAS1096 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS109626 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-812-8646 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1096-2-6 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.344 Inches Minimum And 0.406 Inches Maximum |
| Fastener Length: | 0.359 Inches Minimum And 0.406 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.096 Inches Minimum And 0.110 Inches Maximum |
| Width Between Flats: | 0.241 Inches Minimum And 0.250 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 8630 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1096-2-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.