

Description

length: 9/16", thread: 8-32, hex head screw, recessed, full thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS109629
Minimum Qty (MOQ):	100
NSN:	5305-00-825-3443
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1096-2-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.475 Inches Minimum
Fastener Length:	0.546 Inches Minimum And 0.593 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.241 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1906 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1096-2-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.