



Military-Fasteners.com

P/N NAS1096-3-3

Description

Fastener Length: 3/16", Thread: 10-32, Thread Length: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS109633
Minimum Qty (MOQ):	85 EA
NSN:	5305-00-889-6921
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1096-3-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.124 Inches Minimum And 0.156 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.302 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1096-3-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.