

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097AD315D |
| Minimum Qty (MOQ): | 505 EA |
| NSN: | 5320-01-542-5404 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD3-15D Specifications

| | |
|---|--|
| Fastener Length: | 0.937 Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.140 Inches Minimum And 0.147 Inches Maximum |
| Head Minor Diameter: | 0.091 Inches Minimum And 0.096 Inches Maximum |
| Countersink Height: | 0.021 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Part Name Assigned By Controlling Agency: | Rivet, Solid, 100 Deg Flush Shear Head |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | 2117-t4 Aluminum Alloy National Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Ty II, Cl 1, Color Yellow Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.