

## P/N NAS1097AD3-16D

### **Description**

Fastener Length: 1-"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1097AD316D

Minimum Qty (MOQ): 505 EA

NSN: 5320-01-525-5270

Schedule B: 7616.10.3000

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1097AD3-16D Specifications

Fastener Length:	1.000 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.141 Inches Minimum And 0.148 Inches Maximum
Head Minor Diameter:	0.086 Inches Minimum And 0.096 Inches Maximum
Countersink Height:	0.021 Inches Nominal
End Item Identification:	F-15 Aircraft
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall And Chromate Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D">https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D">https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D">https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D">https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-16D</a> and selecting the quantity you want of the property o