

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1097AD33D                              |
| Minimum Qty (MOQ):      | 1000 EA                                   |
| NSN:                    | 5320-01-423-4748                          |
| Schedule B:             | 7616.10.3000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1097AD3-3D Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 0.178 Inches Minimum And 0.198 Inches Maximum                      |
| <b>Head Style:</b>                                    | Undersized Oval Countersunk  |
| <b>Head Height:</b>                                   | 0.003 Inches Minimum And 0.005 Inches Maximum                      |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.096 Inches Maximum                      |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                                    |
| <b>Head Major Diameter:</b>                           | 0.1263 Inches Minimum And 0.1478 Inches Maximum                    |
| <b>Head Minor Diameter:</b>                           | 0.086 Nominal Mils And 0.096 Nominal Centimeters                   |
| <b>Countersink Height:</b>                            | 0.0089 Inches Minimum And 0.0123 Inches Maximum                    |
| <b>Countersink Angle:</b>                             | 70.0 Degrees Minimum And 130.0 Degrees Maximum                     |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall                                  |
| <b>Material:</b>                                      | Aluminum Alloy 2117 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625, Ty li, Cl 1 Mil Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1097 Professional/industrial Association Standard         |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-3D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.