

**Description**

length: 1/4" diameter: 3/32", flush shear head, 2117-t4 aluminum alloy, roughly 5000 pieces per pound, NAS1097 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1097AD34
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-264-4208
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1097AD3-4 Specifications

<b>Fastener Length:</b>	0.250 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.094 Inches Nominal
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.126 Inches Minimum And 0.148 Inches Maximum
<b>Head Minor Diameter:</b>	0.086 Inches Minimum And 0.096 Inches Maximum
<b>Countersink Height:</b>	0.021 Inches Nominal
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/Industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.