

Description

Fastener Length: 1/4", roughly 5000 pieces per pound, NAS1097 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD34D
Minimum Qty (MOQ):	100
NSN:	5320-01-426-3142
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1097AD3-4D Specifications

Fastener Length:	0.240 Inches Minimum And 0.250 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1263 Inches Minimum And 0.1478 Inches Maximum
Head Minor Diameter:	0.086 Nominal Mils And 0.096 Nominal Centimeters
Countersink Height:	0.0089 Inches Minimum And 0.0123 Inches Maximum
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty2, Cl1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.