

Description

Length: 5/16" diameter: 3/32", flush shear head, aluminum alloy, roughly 4450 pieces per pound, NAS1097 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1097AD35 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-071-5926 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1097AD3-5 Specifications

| | |
|---|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.096 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.141 Inches Minimum And 0.148 Inches Maximum |
| Head Minor Diameter: | 0.086 Inches Minimum And 0.096 Inches Maximum |
| Countersink Height: | 0.021 Inches Nominal |
| Grip Length: | 0.171 Inches Nominal |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.