

## P/N NAS1097AD4-12D

### **Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1097AD412D

Minimum Qty (MOQ): 65 EA

NSN: 5320-01-522-1761

Schedule B: 7616.10.3000

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1097AD4-12D Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.188 Inches Minimum And 0.195 Inches Maximum
Head Minor Diameter:	0.134 Inches Minimum And 0.144 Inches Maximum
Countersink Height:	0.031 Inches Nominal
End Item Identification:	Aircraft, Hornet F/a-18(e/f)
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-12D">https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-12D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.