

**Description**

length: 7/32" diameter: 1/8", flush shear head, aluminum alloy, roughly 3150 pieces per pound, NAS1097 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1097AD435
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-578-9935
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1097AD4-3.5 Specifications

<b>Fastener Length:</b>	0.219 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.127 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.188 Inches Minimum And 0.196 Inches Maximum
<b>Head Minor Diameter:</b>	0.134 Inches Minimum And 0.144 Inches Maximum
<b>Countersink Height:</b>	0.032 Inches Minimum And 0.034 Inches Maximum
<b>Countersink Angle:</b>	70.0 Degrees Minimum And 130.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid, 100 Deg, Flush Shear Head, Aluminum Alloy
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Class 1a. Yellow Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-3.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.