

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD43D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-423-4747
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1097AD4-3D Specifications

Identification Code Color:	Yellow
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1742 Inches Minimum And 0.1957 Inches Maximum
Head Minor Diameter:	0.134 Nominal Mils And 0.144 Nominal Centimeters
Countersink Height:	0.0106 Inches Minimum And 0.0141 Inches Maximum
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty II, Cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-3D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.