

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1097AD44A |
| Minimum Qty (MOQ): | 1000 EA |
| NSN: | 5320-01-489-1178 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N NAS1097AD4-4A Specifications

| | |
|---|--|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.188 Inches Minimum And 0.195 Inches Maximum |
| Head Minor Diameter: | 0.134 Inches Minimum And 0.144 Inches Maximum |
| Countersink Height: | 0.031 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Ty 11, Cl 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.