

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD44D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-527-4869
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1097AD4-4D Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.188 Inches Minimum And 0.195 Inches Maximum
End Item Identification:	Aircraft, Hornet F/a-18 (e/f)
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type2.mil-a-8625, Type2 Class 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205 - Nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.