

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD44D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-527-4869
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1097AD4-4D Specifications

<b>Fastener Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.127 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.188 Inches Minimum And 0.195 Inches Maximum
<b>End Item Identification:</b>	Aircraft, Hornet F/a-18 (e/f)
<b>Countersink Angle:</b>	70.0 Degrees Minimum And 130.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Type2.mil-a-8625, Type2 Class 1 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205 - Nas1097 Professional/Industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.