

P/N NAS1097AD4-5

Description

length: 5/16" diameter: 1/8", flush shear head, 2117-t4 aluminum alloy, roughly 2300 pieces per pound, NAS1097 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1097AD45

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-264-4461

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N NAS1097AD4-5 Specifications

| Fastener Length: | 0.312 Inches Nominal |
|---------------------------------------|------------------------------------------------------|
| Head Style: | Oval Countersunk |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.188 Inches Minimum And 0.196 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Mil-w-7986 Mil Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.