

Description

length: 5/16" diameter: 1/8", flush shear head, 2117-t4 aluminum alloy, roughly 2300 pieces per pound, NAS1097 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097AD45 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-264-4461 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N NAS1097AD4-5 Specifications

| | |
|--|--|
| Fastener Length: | 0.312 Inches Nominal |
| Head Style: | Oval Countersunk |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.188 Inches Minimum And 0.196 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Mil-w-7986 Mil Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.