

Description

length: 11/32" diameter: 1/8", flush shear head, 2117-t4 aluminum alloy, roughly 2130 pieces per pound, NAS1097 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD455
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-292-3346
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1097AD4-5.5 Specifications

Fastener Length:	0.333 Inches Minimum And 0.353 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1957 Inches Maximum
Head Minor Diameter:	0.134 Nominal Mils And 0.144 Nominal Centimeters
Countersink Height:	0.0286 Inches Nominal
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-5.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.