

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097AD45D |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-527-3998 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD4-5D Specifications

| | |
|---|---|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.127 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.188 Inches Minimum And 0.195 Inches Maximum |
| End Item Identification: | Aircraft, Hornet F/a-18 (e/f) |
| Countersink Angle: | 70.0 Degrees Minimum And 130.0 Degrees Maximum |
| Special Features: | One Pound Equals 2,455 Rivets |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type Ii0.mil-a-8625, Type Ii0 Class 1 Mil Std Single Treatment Response Overall |
| Specification/standard Data: | 80205 - Nas1097 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.