

P/N NAS1097AD4-6

Description

length: 3/8" diameter: 1/8", flush shear head, aluminum alloy, NAS1097 series rivet, roughly 1955 pieces per pound

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1097AD46

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-889-2495

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets









^{*} See page 2 for technical characteristics

P/N NAS1097AD4-6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.007 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.174 Inches Minimum And 0.196 Inches Maximum
Head Minor Diameter:	0.134 Nominal Mils And 0.144 Nominal Centimeters
Countersink Height:	0.029 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-6 and selecting the quantity you want then