

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD47D
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-451-6829
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1097AD4-7D Specifications

Identification Code Color:	Yellow
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1742 Inches Minimum And 0.1957 Inches Maximum
Head Minor Diameter:	0.134 Nominal Mils And 0.144 Nominal Centimeters
Countersink Height:	0.0106 Inches Minimum And 0.0141 Inches Maximum
End Item Identification:	F-15s
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Criticality Code Justification:	Agav
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty li, Cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD4-7D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.