

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD512D
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-582-7531
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD5-12D Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Nominal
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.239 Inches Minimum And 0.247 Inches Maximum
Head Minor Diameter:	0.190 Inches Nominal
Countersink Height:	0.037 Inches Nominal
End Item Identification:	F-15 Aircraft
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type II,class 1(dichromate Seal)color Yellow Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD5-12D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.