

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD54D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-546-7636
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1097AD5-4D Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2396 Inches Minimum And 0.2469 Inches Maximum
Head Minor Diameter:	0.185 Inches Minimum And 0.195 Inches Maximum
Countersink Height:	0.0372 Inches Nominal
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet,solid
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD5-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.