

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD55A
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-452-7917
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N NAS1097AD5-5A Specifications

Fastener Length:	0.312 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.2396 Inches Minimum And 0.2469 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Comp T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty li, Cl 1, Clear Mil Spec Single Treatment Response Overall
Specification/standard Data:	8205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD5-5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.