

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097AD55D |
| Minimum Qty (MOQ): | 335 EA |
| NSN: | 5320-01-496-5344 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD5-5D Specifications

| | |
|---|---|
| Fastener Length: | 0.312 Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.2396 Inches Minimum And 0.2469 Inches Maximum |
| Head Minor Diameter: | 0.185 Inches Minimum And 0.195 Inches Maximum |
| Countersink Height: | 0.0372 Inches Nominal |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type II, Class 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD5-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.