

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD56D
Minimum Qty (MOQ):	200 EA
NSN:	5320-00-917-2709
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



NO IMAGE  
AVAILABLE

## P/N NAS1097AD5-6D Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.247 Inches Maximum
<b>Head Minor Diameter:</b>	0.185 Inches Minimum And 0.195 Inches Maximum
<b>Countersink Height:</b>	0.037 Inches Nominal
<b>Grip Length:</b>	0.141 Inches Nominal
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD5-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.