

Description

length: 7/8" diameter: 3/16", flush shear head 2117-t4 aluminum alloy, roughly 390 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD614
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-864-6112
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1097AD6-14 Specifications

Fastener Length:	0.875 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.188 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.275 Inches Minimum And 0.302 Inches Maximum
Head Minor Diameter:	0.198 Nominal Mils And 0.208 Nominal Centimeters
Countersink Height:	0.046 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.