

Description

length: 7/8" diameter: 3/16", flush shear head 2117-t4 aluminum alloy, roughly 390 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097AD614 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-864-6112 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N NAS1097AD6-14 Specifications

| | |
|---|---|
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.004 Inches Minimum And 0.006 Inches Maximum |
| Shank Diameter: | 0.188 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.275 Inches Minimum And 0.302 Inches Maximum |
| Head Minor Diameter: | 0.198 Nominal Mils And 0.208 Nominal Centimeters |
| Countersink Height: | 0.046 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.