



Military-Fasteners.com

P/N NAS1097AD6-2

Description

length: 1/8" diameter: 3/16", 100°, flush shear head - 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD62
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-554-2936



* See page 2 for technical characteristics

P/N NAS1097AD6-2 Specifications

Fastener Length:	0.1255 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Head Minor Diameter:	0.198 Inches Minimum And 0.208 Inches Maximum
Countersink Height:	0.046 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-p-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.