

Description

length: 15/32" diameter: 3/16", flush shear head, 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

NAS1097AD6-7-5

SKU / Model:	NAS1097AD675
Minimum Qty (MOQ):	100
NSN:	5320-01-447-0503
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1097AD6-7.5 Specifications

Fastener Length:	0.459 Inches Minimum And 0.479 Inches Maximum
Head Style:	Shovel
Head Height:	0.037 Inches Nominal
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.239 Inches Minimum And 0.246 Inches Maximum
Countersink Height:	0.015 Inches Minimum And 0.018 Inches Maximum
Material:	Titanium Alloy Uns R56400 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-7.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.