

Description

length: 9/16" diameter: 3/16", flush shear head, 2117-t4 aluminum alloy, roughly 588 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD69
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-864-6116
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N NAS1097AD6-9 Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.3016 Inches Maximum
Head Minor Diameter:	0.198 Nominal Mils And 0.208 Nominal Centimeters
Countersink Height:	0.046 Inches Nominal
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.