

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD83
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-542-3327
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD8-3 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.188/ Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.3756 Inches Minimum And 0.3948 Inches Maximum
Head Minor Diameter:	0.316 Inches Minimum And 0.326 Inches Maximum
Countersink Height:	0.0232 Inches Minimum And 0.0278 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Finish:chemical Conversion Per Mil-c-5541, Class 1a
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.