

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097AD83 |
| Minimum Qty (MOQ): | 200 EA |
| NSN: | 5320-01-542-3327 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097AD8-3 Specifications

| | |
|--|--|
| Identification Code Color: | Yellow |
| Fastener Length: | 0.188/ Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.004 Inches Minimum And 0.006 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.252 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.3756 Inches Minimum And 0.3948 Inches Maximum |
| Head Minor Diameter: | 0.316 Inches Minimum And 0.326 Inches Maximum |
| Countersink Height: | 0.0232 Inches Minimum And 0.0278 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Finish:chemical Conversion Per Mil-c-5541, Class 1a |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Specification/standard Data: | 80205-nas1097 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.