

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097AD83
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-542-3327
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1097AD8-3 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.188/ Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Minimum And 0.006 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.252 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.3756 Inches Minimum And 0.3948 Inches Maximum
<b>Head Minor Diameter:</b>	0.316 Inches Minimum And 0.326 Inches Maximum
<b>Countersink Height:</b>	0.0232 Inches Minimum And 0.0278 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Finish:chemical Conversion Per Mil-c-5541, Class 1a
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.