



★ FASTENERS

Military-Fasteners.com

P/N NAS1097AD8-8

Description

length: 1/2" diameter: 1/4", flush shear head, aluminum alloy, roughly 330 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1097AD88 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-255-5029 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1097AD8-8 Specifications

| | |
|---|--|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.004 Inches Minimum And 0.006 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.252 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.3948 Inches Maximum |
| Head Minor Diameter: | 0.316 Nominal Mils And 0.326 Nominal Centimeters |
| Countersink Height: | 0.060 Inches Nominal |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1097 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.