

**Description**

Fastener Length: 0-63/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1097B316         |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-390-0731    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N NAS1097B3-16 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.990 Inches Minimum And 1.010 Inches Maximum  |
| <b>Head Style:</b>                                    | Undersized Oval Countersunk  |
| <b>Head Height:</b>                                   | 0.003 Inches Minimum And 0.005 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.096 Inches Maximum  |
| <b>Shank Style:</b>                                   | Straight   |
| <b>Head Major Diameter:</b>                           | 0.126 Inches Minimum And 0.148 Inches Maximum  |
| <b>Head Minor Diameter:</b>                           | 0.086 Inches Minimum And 0.096 Inches Maximum  |
| <b>Countersink Height:</b>                            | 0.021 Inches Nominal   |
| <b>Shear Strength:</b>                                | 24000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum   |
| <b>Heat Treatment:</b>                                | H-32 Strain Hardened Overall   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Overall  |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Oxide Film Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1097 Professional/industrial Association Standard   |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B3-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.