

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097B34A |
| Minimum Qty (MOQ): | 1000 EA |
| NSN: | 5320-01-393-7791 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1097B3-4A Specifications

| | |
|--|---|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Shovel |
| Head Height: | 0.021 Inches Nominal |
| Shank Diameter: | 0.093 Inches Minimum And 0.095 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.1405 Inches Minimum And 0.1478 Inches Maximum |
| Countersink Height: | 0.003 Inches Minimum And 0.006 Inches Maximum |
| Material: | Aluminum Alloy 5056 Overall |
| Material Document And Classification: | Mil-r-5674 Mil Std Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B3-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.