

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097B38A
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-426-3156
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N NAS1097B3-8A Specifications

<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.096 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.1478 Inches Maximum
<b>Head Minor Diameter:</b>	0.086 Nominal Mils And 0.096 Nominal Centimeters
<b>Countersink Height:</b>	0.021 Inches Nominal
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Ty 2, Cl 1 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B3-8A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.